

SWINGING FULL LENGTH DOORS



BT72SD

FEATURES

- Top-mounted condensing unit supplied with quick connects and an attractive cover.
- Automatic condensate evaporator standard on top mounted model.
- All remotes equipped with expansion valves - Specify refrigerant when ordering.
- Rigid all welded exterior with powder coat finish.
- Back anodized aluminum, self-closing swinging doors with heated frames and jambs.
- Double paned tempered insulated glass.
- Switch-controlled vertical fluorescent lamps.
- Adjustable heavy duty white epoxy wire shelves with front product stop.
- Stainless steel bottom pans.
- Environmentally friendly refrigerants.

REMOTE	BR54SD	BR72SD	BR79SD	BR103SD	BR127SD	BR138SD	BR172SD
Width	54"	72"	79½"	103"	126 ¾"	138 ½"	172 ½"
Depth	31"	31"	31"	31"	31"	31"	31"
Height	74 ½"	74 ½"	74 ½"	74 ½"	74 ½"	74 ½"	74 ½"
Volume/cu. ft.	51	70	77	103	128	140	175
Doors	2	2	3	4	5	4	5
Door Size	23" X 66"	31" X 66"	23" X 66"	23" X 66"	23" X 66"	31" X 66"	31" X 66"
Shelves	10	10	15	20	25	20	25
Unit HP req'd	½	½	½ +	¾	1	1	1 ½
Voltage	115	115	115	115	115	115	115
Amps	4	5	5	6	8	10	12
Lights	3	3	4	5	6	5	6
Shipping Weight	560#	700#	800#	1000#	1450#	1600#	1800#
TOP MOUNTED	BT54SD	BT72SD	BT79SD	BT103SD	BT127SD	BT138SD	BT172SD
Height w/ Compressor	86 ½"	86 ½"	86 ½"	88 ½"	88 ½"	88 ½"	88 ½"
Voltage-top mounted	115	115	115	230/115	230/115	230/115	230/115
Amps top mounted	10	12	17	8/13	8/13	8/13	10/15



105 Steamboat Drive • Warminster, PA 18974
 Phone (215) 675-9220 • (800) 673-7868 • Fax (215) 675-0878
 Website: powersequipment.com