

MILK CASE COOLERS

Serve milk directly from the case on a cafeteria line, or use as back room storage in high volume stops. Reduce labor and delivery time. Unique lid arrangement offers lowest serving height in the industry. Long lasting aluminum interior is standard in a Powers, for most efficient cold wall cooling.



681 (closed)

569 (open)

780 (closed)

Features:

- NSF and ETL approved.
- Powder-coat or stainless steel exterior finish.
- All copper tubing.
- Removable plastic, easily cleanable bottom pans.
- Vinyl gasket is removable without tools.
- 2" Non-CFC foamed-in-place polyurethane insulated cabinet and lids.
- Slam latches on lower lid (optional lock).
- Stainless steel hinges and latches.
- Energy efficient - no interior fan.
- Low maintenance.
- Self contained, ready to plug in.
- 2" dial thermometer.
- Bottom drain.
- 8 foot power cord, 115V 60HZ.
- Stainless steel top and lids; heavy gauge, aluminum interior.
- 1/5 HP condensing unit, CFC-free R134A refrigerant.

| DESCRIPTION | 681 | 569 | 780 |
|------------------------------|-------|-------|-------|
| Width | 33" | 47" | 59" |
| Depth | 31" | 31" | 31" |
| Height | 40½" | 40½" | 40½" |
| Volume/cu. ft. | 11.2 | 16.7 | 21.4 |
| Unit HP req'd | 1/5 | 1/5 | 1/5 |
| Voltage | 115 | 115 | 115 |
| Amps | 4 | 4 | 4 |
| Bottom Racks | 2 | 3 | 4 |
| Interior width | 28 ¾" | 42 ¾" | 54 ¾" |
| Interior depth | 27" | 27" | 27" |
| Interior height | 25" | 25" | 25" |
| Shipping Weight | 220# | 270# | 320# |
| CAPACITY | | | |
| 13 x 13 case 16 qt. capacity | 8 | 12 | 16 |
| 13 x 16 case 20 qt. capacity | 4 | 8 | 12 |
| 13 x 19 case 24 qt. capacity | 4 | 8 | 10 |



105 Steamboat Drive • Warminster, PA 18974
 Phone (215) 675-9220 • (800) 673-7868 • Fax (215) 675-0878
 Website: powersequipment.com • Email: sales@powersequipment.com