

# STORAGE REFRIGERATORS



## FEATURES

- 2" foamed-in-place polyurethane insulation.
- All welded exterior, galvanized interior.
- Foamed-in-place stainless steel door with magnetic gasket.
- Inside door release latch.
- Supplied with crankcase heater and fan cycling control on condensing unit for cold weather operation.
- Larger model can have two doors - load one side, unload another.
- Environmentally friendly refrigerants.
- BT103 supplied with quick connects on condensing unit.



DESCRIPTION	BT70	BT103	BT103-2DR
Width	70"	103"	103"
Depth	30"	30"	30"
Height	74 ½"	74 ½"	74 ½"
Door Size	26" X 67"	26" X 67"	26" X 67"
Volume/Cu. Ft.	74	108	108
Unit HP	1/3	1/2	1/2
Voltage	115	115	115
Amps	11	12	12
Weight	750#	1100#	1100#



**POWERS**

Equipment Company, Inc.

REFRIGERATED EQUIPMENT MANUFACTURERS

105 Steamboat Drive • Warminster, PA 18974

Phone (215) 675-9220 • (800) 673-7868 • Fax (215) 675-0878

Website: [powersequipment.com](http://powersequipment.com) • Email: [sales@powersequipment.com](mailto:sales@powersequipment.com)