

MILK CASE COOLERS

Serve milk directly from the case on a cafeteria line, or use as back room storage in high volume stops. Reduce labor and delivery time. Unique lid arrangement offers lowest serving height in the industry. Long lasting aluminum interior is standard in a Powers, for most efficient cold wall cooling.



681 (closed)



569 (open)



780 (closed)

Features:

- NSF and ETL approved.
- Powder-coat or stainless steel exterior finish.
- All copper tubing.
- Removable plastic, easily cleanable bottom pans.
- Vinyl gasket is removable without tools.
- 2" Non-CFC foamed-in-place polyurethane insulated cabinet and lids.
- Slam latches on lower lid.
- Stainless steel hinges and latches.
- Casters.
- 1/5 HP condensing unit, CFC-free R134A refrigerant.
- Energy efficient - no interior fan.
- Low maintenance.
- Self contained, ready to plug in.
- 2" dial thermometer.
- Bottom drain.
- 8 foot power cord, 115V 60HZ.
- Stainless steel top and lids; heavy gauge, aluminum interior.
- One year parts and labor warranty
- Five year compressor warranty

DESCRIPTION	681	569	780
Width	33"	47"	59"
Depth	31"	31"	31"
Height	40½"	40½"	40½"
Volume/cu. ft.	11.2	16.7	21.4
Unit HP req'd	1/5	1/5	1/5
Voltage	115	115	115
Amps	3.7	3.7	3.7
Bottom Racks	2	3	4
Interior width	28 ¾"	42 ¾"	54 ¾"
Interior depth	27"	27"	27"
Interior height	25"	25"	25"
Shipping Weight	220#	270#	320#
CAPACITY			
13 x 13 case 16 qt. capacity	8	12	16
13 x 16 case 20 qt. capacity	4	8	12
13 x 19 case 24 qt. capacity	4	8	10



REFRIGERATED EQUIPMENT MANUFACTURERS

105 Steamboat Drive • Warminster, PA 18974

Phone (215) 675-9220 • (800) 673-7868 • Fax (215) 675-0878

Website: powersequipment.com • Email: sales@powersequipment.com