

# REFRIGERATED EQUIPMENT MANUFACTURERS

105 Steamboat Drive ● Warminster, PA 18974 ● (215) 675-9220 ● (800) 673-7868

Email: sales@powersequipmemt.com • Website: powersequipment.com

Project Name:		AIA#
Location:		
Item #	Qty:	SIS#
Model #:		

Model:

PCF26SD

## SWING DOOR PHARMA STORAGE COOLER/FREEZER





#### STANDARD FEATURES

- ➤ Self contained ready to plug in.
- ➤ Heavy duty stainless steel door with handle.
- ➤ Custom "Powers Seal" Gasket assures that outside air will not infiltrate the refrigerator unless opened.
- ➤ Door lock included.
- ➤ Powder-coat exterior finish.
- ➤ Digital temperature control allows for control as a freezer or refrigerator
- ➤ Data logger included to allow monitoring of temperatures. Allows for a PDF. report output of stored products temperature range.
- ➤ Cold wall refrigeration technology allows for consistent temperatures. No fan required.
- Switch controlled vertical LED lamp.
- >Adjustable coated wire shelving.
- ➤ Balanced refrigeration/freezer systems allows for a temperature range range from -20°C to 3°C(-4°F to 38°F) with a 2 degree differential from set point. (Note: Unit set at 3°C (37.5°F) at factory)
- >Stainless steel bottom floor.
- The entire cabinet is foamed in place using a high density, CFC free polyurethane insulation providing excellent efficiency.
- ➤ Environmentally safe R290 Refrigerant



		Cabinet Dimensions		Door Size				Plug					
Model	Doors	W	D	Н	W	Н	Shelves	HP	Type	Voltage	Amps	Lights	Crated Weight
DOESCOD	4	0.611	2211	F.C."	0.4.5.11	12 75"		1 /0	5 455	445 100 14	7.0		240 !!
PCF26SD	1	26"	22"	56"	24.5"	43.75"	3	1/3	5-15P	115/60/1	7.0	1	210 lbs

## SWING DOOR PHARMA STORAGE COOLER/FREEZER


## PCF26SD



STANDARD ACCESSORIES 3 Shelves as pictured 7 Day Data logger with PDF report output

**OPTIONAL ACCESSORIES** Casters Full Stainless exterior/interior Stainless steel shelf trays

## STANDARD COLORS White/Black/Gray/Vanilla







Data Logger (standard accessory)



Stainless Steel shelf trays (optional Accessory)







## WARRANTY

#### One Year Parts and Labor

- The warranty is in effect for one year from date of shipment.
- Factory service authorization must be obtained before any work may be performed under the labor warranty.
- The warranty covers reasonable labor costs, based on straight time, when the unit has been diagnosed as defective.
- This warranty does not cover original installation, initial start-up, normal adjustments, or maintenance.
- OEM parts needed for warranty must be obtained from Powers Equipment.

## **Five Year Compressor Warranty**

Powers warrants to the orignal purchaser for a period of five years from the date of shipment, that we will replace the compressor on the unit if found, in the reasonable opinion of the factory, to be defective in material or workmanship. Relays, overloads, capacitors, and any other electrical components are not included in the five-year compressor warranty.

#### **ELECTRICAL REQUIREMENTS**

Cooler is pre-wired at factory and ready for connection to a 115/60/1 phase, 15 amp dedicated outlet.



